

WHAT IS CLAIMED IS:

1. A retractable handle assembly for a luggage, the handle assembly including an elongate handle unit and a handle grip on a top of the handle unit, the handle grip having a push button, the handle unit comprising:
 - 5 a sliding tube connected to the handle grip;
 - a support tube fixed at a bottom of the luggage, the sliding tube being slidably disposed in the support tube;
 - locking means in a lower portion of the sliding tube;
 - 10 a connecting rod interconnected the push button and the locking means;
 - and
 - buffer means within a lower portion of the sliding tube,
 - wherein the handle grip is capable of gradually and damply extending from a top of the luggage a predetermined distance by pressing the push button in a pulling operation of the handle assembly.
 - 15
2. The retractable handle assembly of claim 1, wherein the buffer means comprises an upper plunger, a spring anchored in the plunger, a piston rod inserted in the spring, a sealing ring anchored on a top of the piston rod, a lower n-shaped bifurcation urged against a bottom of the spring, and a pin hingedly coupled a top of the n-shaped bifurcation and a bottom of the piston rod together.- 20
3. The retractable handle assembly of claim 2, wherein the plunger comprises an upper body, a vent hole on a top of the upper body, a pair of lower arms, and a hole at a lower portion of either arm.- 25
4. The retractable handle assembly of claim 2, wherein the piston rod

comprises an upper neck, an intermediate body, and a bottom tunnel.

5 5. The retractable handle assembly of claim 2, wherein the n-shaped bifurcation comprises two legs and two spaced top cylindrical members each having a tunnel.

6. The retractable handle assembly of claim 1, wherein the sliding tube comprises two upper holes for permitting a fastener to insert through to secure to the luggage, two intermediate locking apertures, and two opposite lower holes.

10

7. The retractable handle assembly of claim 1, wherein the support tube comprises an upper locking aperture, an intermediate locking aperture, and a lower hole.

15 8. A retractable handle assembly for a luggage, the handle assembly including a pair of elongate substantially parallel handle units and a handle grip interconnected the handle units, the handle grip having a push button, either of the handle units comprising:

20 a sliding tube connected to one end of the handle grip;
 a support tube fixed at a bottom of the luggage, the sliding tube being slidably disposed in the support tube;

locking means in a lower portion of the sliding tube;

a connecting rod interconnected the push button and the locking means;

and

25 buffer means within a lower portion of the sliding tube,

wherein the handle grip is capable of gradually and damply extending from a top of the luggage a predetermined distance by pressing the push button in a

pulling operation of the handle assembly.

5 **9.** The retractable handle assembly of claim 8, wherein the buffer means comprises an upper plunger, a spring anchored in the plunger, a piston rod inserted in the spring, a sealing ring anchored on a top of the piston rod, a lower n-shaped bifurcation urged against a bottom of the spring, and a pin hingedly coupled a top of the n-shaped bifurcation and a bottom of the piston rod together.

10 **10.** The retractable handle assembly of claim 9, wherein the plunger comprises an upper body, a vent hole on a top of the upper body, a pair of lower arms, and a hole at a lower portion of either arm.

15 **11.** The retractable handle assembly of claim 9, wherein the piston rod comprises an upper neck, an intermediate body, and a bottom tunnel.

12. The retractable handle assembly of claim 9, wherein the n-shaped bifurcation comprises two legs and two spaced top cylindrical members each having a tunnel.